

SRFV<UL STYLE 20949> 600V 105°C定格 同心撚りケーブル

※外径、概算質量の()内はシールド付の値

型式	導体		ETFE絶縁体	線心数 (本)	PVCシース	概算質量 (kg/km)	電気特性※2			許容電流 周囲温度40°C以下 / 気中施設の場合 (A以下)	
	サイズ(断面積)	構成	標準外径		標準外径		導体抵抗 (Ω/m以下)	絶縁抵抗 (MΩ·km以上)	耐電圧※1 V/1分間		
	AWG. (mm ²)	本/mm	(mm)		(mm)						
SRFV-A075C02 (S)				2	7.5 (7.9)	69 (83)				13.5	
SRFV-A075C03 (S)				3	8.0 (8.4)	85 (99)				11.7	
SRFV-A075C04 (S)				4	8.6 (9.0)	103 (118)				10.4	
SRFV-A075C06 (S)	19 (0.774)	7/22/0.08	2.00	6	9.5 (9.9)	135 (153)	0.026				8.8
SRFV-A075C10 (S)				10	12.6 (13.2)	221 (258)					7.2
SRFV-A075C12 (S)				12	14.1 (14.9)	265 (312)					6.1
SRFV-A075C15 (S)				15	13.6 (14.2)	290 (330)					6.1
SRFV-A075C20 (S)				20	15.1 (15.7)	372 (414)					5.4
SRFV-A125C02 (S)				2	8.1 (8.5)	87 (101)				18.7	
SRFV-A125C03 (S)				3	8.7 (9.1)	110 (125)				16.2	
SRFV-A125C04 (S)				4	9.4 (9.8)	134 (152)				14.5	
SRFV-A125C06 (S)	17 (1.266)	7/36/0.08	2.40	6	10.4 (10.8)	179 (198)	0.016				12.2
SRFV-A125C10 (S)				10	14.0 (14.8)	298 (344)					10.0
SRFV-A125C12 (S)				12	15.9 (16.7)	364 (416)					8.5
SRFV-A125C15 (S)				15	15.4 (16.2)	405 (457)					8.5
SRFV-A125C20 (S)				20	17.1 (17.9)	522 (577)					7.5
SRFV-A200C02 (S)				2	9.2 (9.6)	115 (131)		2,500	1,500	24.8	
SRFV-A200C03 (S)				3	10.0 (10.4)	149 (168)				21.5	
SRFV-A200C04 (S)				4	10.8 (11.4)	184 (209)				19.1	
SRFV-A200C06 (S)	15 (2.005)	7/57/0.08	2.90	6	12.1 (12.7)	253 (289)	0.011				16.2
SRFV-A200C10 (S)				10	16.7 (17.3)	432 (478)					13.2
SRFV-A200C12 (S)				12	18.9 (19.8)	527 (600)					11.2
SRFV-A200C15 (S)				15	18.3 (18.9)	590 (640)					11.2
SRFV-A200C20 (S)				20	20.3 (21.2)	760 (837)					9.9
SRFV-A350C02 (S)				2	10.7 (11.3)	170 (195)				38.8	
SRFV-A350C03 (S)				3	11.8 (12.2)	230 (251)				33.7	
SRFV-A350C04 (S)				4	12.9 (13.5)	289 (326)				30.1	
SRFV-A350C06 (S)	12 (3.694)	7/105/0.08	3.60	6	14.5 (15.1)	403 (444)	0.0055				25.4
SRFV-A350C10 (S)				10	20.3 (21.2)	696 (772)					20.7
SRFV-A350C12 (S)				12	23.2 (23.9)	859 (935)					17.6
SRFV-A350C15 (S)				15	22.2 (23.1)	960 (1,044)					17.6
SRFV-A350C20 (S)				20	24.9 (25.6)	1,254 (1,334)					15.5

型式例 SRFV-A075C02 … シールドなし
SRFV-A075C02S … シールド付

※1 シールド付ケーブルはシールド線心間で2,000V/1分間です。
※2 単心コードでの値です。